

Serial No. 10/604,433  
Filed: 07/21/2003  
Page 2 of 22

Examiner: Jeanette E. Chapman  
Group Art Unit: 3635

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A dormer for attachment to a roof portion of a structure comprising:

a girder frame having a pair of elongated rails, wherein the girder frame is configured to be in register with an opening in an angled roof portion of the structure when the girder frame is mounted to the roof portion of a structure;

a front frame mounted to the girder frame, wherein the front frame is configured to be positioned in a generally vertical orientation when the girder frame is mounted to the roof portion; and

a top frame mounted to the front frame, wherein the top ~~wall~~frame is configured to form a roof for the dormer;

wherein at least two of the girder frame, the front frame, and the top frame are pivotally mounted to one another between a first, lowered position and a second, finished position.

2. (Original) The dormer of claim 1 wherein the front frame is pivotally mounted to the girder frame between a first, lowered position and a second, finished position.

3. (Original) The dormer of claim 2 wherein the top frame is pivotally mounted to the girder frame between a first, lowered position and a second, finished position.

4. (Original) The dormer of claim 3 wherein the top frame is pivotally mounted to the front frame between a first, lowered position and a second, finished position.

Serial No. 10/604,433  
Filed: 07/21/2003  
Page 3 of 22

Examiner: Jeanette E. Chapman  
Group Art Unit: 3635

5. (Original) The dormer of claim 4 wherein the top frame comprises a plurality of first truss members and a plurality of second truss members each pivotally mounted to the top frame.
6. (Original) The dormer of claim 5 wherein the first and second truss members are pivotally moveable relative to the top frame between a first, lowered position and a second raised position, wherein the top frame can be easily transported in a low volume when the first and second truss members are positioned in the first, lowered position.
7. (Original) The dormer of claim 6 and further comprising a top frame ridge board, wherein the first and second truss members are fixedly mounted to the top frame ridge board when the first and second truss members are moved to the second, raised position.
8. (Original) The dormer of claim 7 and further comprising a finishing frame adapted to be mounted between the top frame in the second, finished position and the roof portion of the structure to form a transition between the top frame and the roof portion of the structure.
9. (Original) The dormer of claim 8 and further comprising at least one side frame adapted to be mounted between an upper surface of the girder frame and a lower portion of at least one of the front frame and the top frame, wherein the at least one side frame forms a vertical side wall of the dormer.
10. (Original) The dormer of claim 9 wherein the at least one side frame is mounted to the dormer after all components have been raised to the second, finished position.
11. (Original) The dormer of claim 10 and further comprising at least one knee wall chord for holding the dormer assembly in the second, finished position.
12. (Original) The dormer of claim 11 wherein the knee wall chord is pivotally mounted to the girder frame at a central area thereof.
13. (Original) The dormer of claim 12 wherein the knee wall chord is pivotally mounted to the girder frame between the mountings of the top frame and the front frame.

Serial No. 10/604,433  
Filed: 07/21/2003  
Page 4 of 22

Examiner: Jeanette E. Chapman  
Group Art Unit: 3635

14. (Original) The dormer of claim 1 wherein the top frame is pivotally mounted to the girder frame between a first, lowered position and a second, finished position.
15. (Original) The dormer of claim 1 wherein the top frame is pivotally mounted to the front frame between a first, lowered position and a second, finished position.
16. (Original) The dormer of claim 1 wherein the top frame comprises a plurality of first truss members and a plurality of second truss members each pivotally mounted to the top frame.
17. (Original) The dormer of claim 16 wherein the first and second truss members are pivotally moveable relative to the top frame between a first, lowered position and a second raised position, wherein the top frame can be easily transported in a low volume when the first and second truss members are positioned in the first, lowered position.
18. (Original) The dormer of claim 17 and further comprising a top frame ridge board, wherein the first and second truss members are fixedly mounted to the top frame ridge board when the first and second truss members are moved to the second, raised position.
19. (Original) The dormer of claim 1 and further comprising a finishing frame adapted to be mounted between the top frame in the second, finished position and the roof portion of the structure to form a transition between the top frame and the roof portion of the structure.
20. (Original) The dormer of claim 1 and further comprising at least one side frame adapted to be mounted between an upper surface of the girder frame and a lower portion of at least one of the front frame and the top frame, wherein the at least one side frame forms a vertical side wall of the dormer.
21. (Original) The dormer of claim 20 wherein the at least one side frame is mounted to the dormer after all components have been raised to the second, finished position.
22. (Original) The dormer of claim 1 and further comprising at least one knee wall chord for holding the dormer assembly in the second, finished position.

Serial No. 10/604,433  
Filed: 07/21/2003  
Page 5 of 22

Examiner: Jeanette E. Chapman  
Group Art Unit: 3635

23. (Original) The dormer of claim 22 wherein the knee wall chord is pivotally mounted to the girder frame at a central area thereof.
24. (Original) The dormer of claim 23 wherein the knee wall chord is pivotally mounted to the girder frame between the mountings of the top frame and the front frame.
25. (Original) A dormer assembly for attachment to a roof portion of a structure comprising:  
  
a dormer; and  
  
a hinge attached to the dormer adapted to pivotally mount the dormer to the roof portion of a structure between a collapsed position and a finished, erected position.
26. (Original) The dormer assembly of claim 25 wherein the dormer comprises a girder frame adapted to be interconnected with the hinge and to be located in register with an opening in the roof portion of the structure.
27. (Original) The dormer assembly of claim 26 wherein the dormer comprises a front frame adapted to be positioned in a generally vertical orientation when the girder frame is positioned in the finished, erected position.
28. (Original) The dormer assembly of claim 27 wherein the dormer comprises a top frame adapted to form a roof portion of the dormer assembly when the girder frame is positioned in the finished, erected position.
29. (Original) The dormer assembly of claim 28 wherein the front frame is pivotally mounted to the girder frame between a first, lowered position and a second, finished position.
30. (Original) The dormer assembly of claim 29 wherein the top frame is pivotally mounted to the girder frame between a first, lowered position and a second, finished position.
31. (Original) The dormer assembly of claim 30 wherein the top frame is pivotally mounted to the front frame between a first, lowered position and a second, finished position.

Serial No. 10/604,433  
Filed: 07/21/2003  
Page 6 of 22

Examiner: Jeanette E. Chapman  
Group Art Unit: 3635

32. (Original) The dormer assembly of claim 31 wherein the top frame comprises a plurality of first truss members and a plurality of second truss members each pivotally mounted to the top frame.

33. (Original) The dormer assembly of claim 32 wherein the first and second truss members are pivotally moveable relative to the top frame between a first, lowered position and a second raised position, wherein the top frame can be easily transported in a low volume when the first and second truss members are positioned in the first, lowered position.

34. (Original) The dormer assembly of claim 33 and further comprising a top frame ridge board, wherein the first and second truss members are fixedly mounted to the top frame ridge board when the first and second truss members are moved to the second, raised position.

35. (Original) The dormer assembly of claim 34 and further comprising a finishing frame adapted to be mounted between the top frame in the second, finished position and the roof portion of the structure to form a transition between the top frame and the roof portion of the structure.

36. (Original) The dormer assembly of claim 35 and further comprising at least one side frame adapted to be mounted between an upper surface of the girder frame and a lower portion of at least one of the front frame and the top frame, wherein the at least one side frame forms a vertical side wall of the dormer assembly.

37. (Original) The dormer assembly of claim 36 wherein the at least one side frame is mounted to the dormer assembly after all components have been raised to the second, finished position.

38. (Original) The dormer assembly of claim 37 and further comprising at least one knee wall chord for holding the dormer assembly in the finished, erected position.

39. (Original) The dormer assembly of claim 38 wherein the knee wall chord is pivotally mounted to the girder frame at a central area thereof.

Serial No. 10/604,433  
Filed: 07/21/2003  
Page 7 of 22

Examiner: Jeanette E. Chapman  
Group Art Unit: 3635

40. (Original) The dormer assembly of claim 39 wherein the knee wall chord is pivotally mounted to the girder frame between the mountings of the top frame and the front frame.
41. (Original) The dormer assembly of claim 25 wherein the dormer comprises a front frame adapted to be positioned in a generally vertical orientation when the girder frame is positioned in the finished, erected position.
42. (Original) The dormer assembly of claim 25 wherein the dormer comprises a top frame adapted to form a roof portion of the dormer assembly when the girder frame is positioned in the finished, erected position.
43. (Original) The dormer assembly of claim 25 wherein the front frame is pivotally mounted to the girder frame between a first, lowered position and a second, finished position.
44. (Original) The dormer assembly of claim 25 wherein the top frame is pivotally mounted to the girder frame between a first, lowered position and a second, finished position.
45. (Original) The dormer assembly of claim 25 wherein the top frame is pivotally mounted to the front frame between a first, lowered position and a second, finished position.
46. (Original) The dormer assembly of claim 25 wherein the top frame comprises a plurality of first truss members and a plurality of second truss members each pivotally mounted to the top frame.
47. (Original) The dormer assembly of claim 46 wherein the first and second truss members are pivotally moveable relative to the top frame between a first, lowered position and a second raised position, wherein the top frame can be easily transported in a low volume when the first and second truss members are positioned in the first, lowered position.
48. (Original) The dormer assembly of claim 47 and further comprising a top frame ridge board, wherein the first and second truss members are fixedly mounted to the top frame ridge board when the first and second truss members are moved to the second, raised position.



Serial No. 10/604,433  
Filed: 07/21/2003  
Page 8 of 22

Examiner: Jeanette E. Chapman  
Group Art Unit: 3635

49. (Original) The dormer assembly of claim 25 and further comprising a finishing frame adapted to be mounted between the top frame in the second, finished position and the roof portion of the structure to form a transition between the top frame and the roof portion of the structure.

50. (Original) The dormer assembly of claim 25 and further comprising at least one side frame adapted to be mounted between an upper surface of the girder frame and a lower portion of at least one of the front frame and the top frame, wherein the at least one side frame forms a vertical side wall of the dormer assembly.

51. (Original) The dormer assembly of claim 50 wherein the at least one side frame is mounted to the dormer assembly after all components have been raised to the finished, erected position.

52. (Original) The dormer assembly of claim 25 and further comprising at least one knee wall chord for holding the dormer assembly in the finished, erected position.

53. (Original) The dormer assembly of claim 52 wherein the knee wall chord is pivotally mounted to the girder frame at a central area thereof.

54. (Original) The dormer assembly of claim 53 wherein the knee wall chord is pivotally mounted to the girder frame between the mountings of the top frame and the front frame.

55-85. (Canceled without prejudice)

86. (Original) An erectable dormer assembly for attachment to a roof portion of a structure comprising:

a girder frame adapted to be interconnected to the roof portion of the structure;

a front frame interconnected to the girder frame and adapted to form a visible vertical wall of the dormer assembly; and

Serial No. 10/604,433  
Filed: 07/21/2003  
Page 9 of 22

Examiner: Jeanette E. Chapman  
Group Art Unit: 3635

a top frame interconnected to the girder frame adapted to form a roof portion of the dormer assembly;

wherein at least one of the front frame and the top frame are pivotally interconnected to the girder frame between a first, lowered position and a second, finished position to assist in the easy transportation and erection of the dormer assembly.

87. (Original) The dormer of claim 86 and further comprising a pair of side walls adapted to be interconnected to vertical sidewalls of the dormer.

88. (Original) The dormer of claim 87 wherein both the front frame and the top frame are pivotally mounted to the girder frame.

89. (Original) The dormer of claim 88 wherein the front frame is pivotally mounted to a lower portion of the girder frame.

90. (Original) The dormer of claim 89 wherein the top frame is pivotally mounted to an upper portion of the girder frame.

91. (Original) The dormer of claim 90 and further comprising a hinge portion mounted to a base portion of the girder frame and adapted to be mounted to the roof portion of the structure between a first, lowered position and a second, raised position.

92. (Original) The dormer of claim 91 wherein the roof portion comprises a plurality of floor trusses.

93. (Original) The dormer of claim 92 and further comprising at least one knee wall chord for holding the dormer assembly in the second, raised position.

94. (Original) The dormer of claim 93 wherein the knee wall chord is pivotally mounted to the girder frame at a middle area thereof.



Serial No. 10/604,433  
Filed: 07/21/2003  
Page 10 of 22

Examiner: Jeanette E. Chapman  
Group Art Unit: 3635

95. (Original) The dormer of claim 94 wherein the knee wall chord is pivotally mounted to the girder frame between the mountings of the top frame and the front frame.
96. (Original) The dormer of claim 95 wherein the top frame comprises a plurality of first truss members and a plurality of second truss members each pivotally mounted to the top frame.
97. (Original) The dormer of claim 96 wherein the first and second truss members are pivotally moveable relative to the top frame between a first, lowered position and a second raised position, wherein the top frame can be easily transported in a low volume when the first and second truss members are positioned in the first, lowered position.
98. (Original) The dormer of claim 97 and further comprising a top frame ridge board, wherein the first and second truss members are fixedly mounted to the top frame ridge board when the first and second truss members are moved to the second, raised position.
99. (Original) The dormer of claim 98 and further comprising a finishing frame adapted to be mounted between the top frame in the second, finished position and the roof portion of the structure to form a transition between the top frame and the roof portion of the structure.
100. (Original) The dormer of claim 86 wherein both the front frame and the top frame are pivotally mounted to the girder frame.
101. (Original) The dormer of claim 86 wherein the front frame is pivotally mounted to a lower portion of the girder frame.
102. The dormer of claim 86 wherein the top frame is pivotally mounted to an upper portion of the girder frame.
103. (Original) The dormer of claim 86 and further comprising a hinge portion mounted to a base portion of the girder frame and adapted to be mounted to the roof portion of the structure between a first, lowered position and a second, raised position.

Serial No. 10/604,433  
Filed: 07/21/2003  
Page 11 of 22

Examiner: Jeanette E. Chapman  
Group Art Unit: 3635

104. (Original) The dormer of claim 86 wherein the roof portion comprises a plurality of floor trusses.
105. (Original) The dormer of claim 86 and further comprising at least one knee wall chord for holding the dormer assembly in the second, raised position.
106. (Original) The dormer of claim 105 wherein the knee wall chord is pivotally mounted to the girder frame at a middle area thereof.
107. (Original) The dormer of claim 105 wherein the knee wall chord is pivotally mounted to the girder frame between the mountings of the top frame and the front frame.
108. (Original) The dormer of claim 86 wherein the top frame comprises a plurality of first truss members and a plurality of second truss members each pivotally mounted to the top frame.
109. (Original) The dormer of claim 108 wherein the first and second truss members are pivotally moveable relative to the top frame between a first, lowered position and a second raised position, wherein the top frame can be easily transported in a low volume when the first and second truss members are positioned in the first, lowered position.
110. (Original) The dormer of claim 108 and further comprising a top frame ridge board, wherein the first and second truss members are fixedly mounted to the top frame ridge board when the first and second truss members are moved to the second, raised position.
111. (Original) The dormer of claim 86 and further comprising a finishing frame adapted to be mounted between the top frame in the second, finished position and the roof portion of the structure to form a transition between the top frame and the roof portion of the structure.